



# CONTAINERS TO MEET YOUR SHIPPING NEEDS

**DRY CARGO  
CONTAINERS**



# TAL INTERNATIONAL CORTEN STEEL DRY CONTAINERS

Specified to meet Industry heavy duty requirements and are targeted at long service life.

All Corten design for resistance to damage and corrosion.

- Forklift pockets provided on 20' units to minimize handling damage.
- Floor forklift test to 7,260 kg (16,000 lbs); Floor reinforced to minimize damages from impact.
- Zn Rich paint to minimize corrosion on damaged areas.

<b>NOMINAL RATINGS*</b>			
<b>EQUIPMENT TYPE</b>	<b>40 HIGH CUBE</b>	<b>40 DRY CONTAINER</b>	<b>20 DRY CONTAINER</b>
<b>MAX GROSS WEIGHT</b>	32,500 kg 71,650 lbs	32,500 kg 71,650 lbs	30,480 kg 67,200 lbs
<b>TARE WEIGHT</b>	3,860 kg 8,510 lbs	3,680 kg 8,110 lbs	2,220 kg 4,900 lbs
<b>PAY LOAD</b>	28,640 kg 63,140 lbs	28,820 kg 63,540 lbs	28,260 kg 62,300 lbs
<b>STACKING WEIGHT, ON BOTTOM BOX</b>	216,000 kg 476,194 lbs	216,000 kg 476,194 lbs	216,000 kg 476,194 lbs
<b>STACKING WEIGHT, ONE DOOR OFF</b>	121,911 kg 268,768 lbs	121,911 kg 268,768 lbs	121,911 kg 268,768 lbs

<b>NOMINAL DIMENSIONS*</b>			
<b>INTERNAL</b>			
<b>LENGTH</b>	12,032 mm 473.75 in	12,032 mm 473.75 in	5,898 mm 232.2 in
<b>WIDTH</b>	2,352 mm 92.6 in	2,352 mm 92.6 in	2,352 mm 92.6 in
<b>HEIGHT</b>	2,698 mm 106.2 in	2,393 mm 94.2 in	2,393 mm 94.2 in
<b>DOOR OPENING</b>			
<b>WIDTH</b>	2,340 mm 92.1 in	2,340 mm 92.1 in	2,340 mm 92.1 in
<b>HEIGHT</b>	2,585 mm 101.75 in	2,280 mm 89.75 in	2,280 mm 89.75 in
<b>CUBIC CAPACITY</b>	76.4 m <sub>3</sub> 2,700 cu ft	67.7 m <sub>3</sub> 2,390 cu ft	33.2 m <sub>3</sub> 1,172 cu ft

\*Specifications may vary per unit. Exact dimensions are available on [www.talinternational.com](http://www.talinternational.com)

- *Solutions from an Experienced Market Leader* •
- *Flexible Leasing Options to Fit Your Unique Financial Situation* •
- *Global Presence* •



TAL International Container Corporation • 100 Manhattanville Road • Purchase, NY 10577-2135 • Tel: (914) 251-9000

[www.talinternational.com](http://www.talinternational.com)

Rev. 6/11